



## Specifications Ledvance LED Downlight DN150 14W 1260lm 100D - 840 Cool White | 160mm - IP44 - Emergency 3H

[View Product](#)

### General Information

|                          |                                    |
|--------------------------|------------------------------------|
| SKU                      | 235461                             |
| EAN                      | 4058075204225                      |
| Brand                    | Ledvance                           |
| Manufacturer Name        | DL ALU DN150 14W/4000K WT EM AT 3H |
| Any Lamp all-in warranty | 3 Years                            |
| Average Lifetime (h)     | 50000                              |

### Technical Information

|                             |                     |
|-----------------------------|---------------------|
| Emergency Lighting          | With Emergency Unit |
| Tilttable                   | No                  |
| Technology                  | LED Integrated      |
| Voltage (V)                 | 220-240             |
| Dimmable                    | Not Dimmable        |
| Colour Code                 | 840 Cool White      |
| Colour temperature (Kelvin) | 4000 Cool White     |
| Colour Rendering (Ra)       | 80-89               |
| Colour of Light             | White               |
| Light colour options        | Single Color        |
| Including bulb              | Yes                 |
| Beam Angle (degree)         | 100                 |

|                          |                                       |
|--------------------------|---------------------------------------|
| Luminous Efficacy (lm/W) | 90                                    |
| Power factor             | >0.90                                 |
| Installation Depth (mm)  | 100                                   |
| Unified Glare Rating     | < 28 - for hallways and storage rooms |
| Product Type Category    | LED Downlight                         |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 150               |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | +5 to +40         |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | DN151             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 52  |
| Diameter (mm) | 160 |

## Sensor Information

|                |                                   |
|----------------|-----------------------------------|
| Type of sensor | <b>Why Any-lamp?</b><br>No Sensor |
|----------------|-----------------------------------|



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process