

## Specifications Noxion LED Panel Delta Pro V2.0 30W 4110lm - 865 Daylight | 62.5x62.5cm - UGR <19 - Dali Dimmable



[View Product](#)

### General Information

|                          |                                                                      |
|--------------------------|----------------------------------------------------------------------|
| SKU                      | 238057                                                               |
| EAN                      | 8719157012164                                                        |
| Brand                    | Noxion                                                               |
| Manufacturer Name        | Noxion LED Panel Delta Pro UGR<19 V2.0 DALI 30W 4110lm 6500K 625x625 |
| Any Lamp all-in warranty | 6 Years                                                              |
| Average Lifetime (h)     | 50000                                                                |
| Series                   | Delta Pro                                                            |

### Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 865 Daylight       |
| Colour temperature (Kelvin) | 6500 Daylight      |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Efficacy (lm/W)    | 125                |
| IP-rating                   | IP20               |
| Impact Protection (IK)      | IK02 - 0.20 joule  |

|                       |           |
|-----------------------|-----------|
| Driver Included       | Yes       |
| Power factor          | >0.90     |
| Product Type Category | LED Panel |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |             |
|----------------|-------------|
| LED panel size | 62.5x62.5cm |
| Length (mm)    | 620         |
| Width (mm)     | 620         |
| Height (mm)    | 32          |

## Sensor Information

Type of sensor

No Sensor

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

